



X-15

For demanding environments with space limitations: a versatile display with hard glass protection and multiple video input options that delivers long-lasting performance.

The X-15 is a durable 15" display that is perfect for any environment where space is at a premium. In busy public environments, the NeoV™ Optical Glass protects the display from incidental damage. The attractive metal casing ensures the durability and strength that allow for secure mounting just about anywhere. With built-in video support and multiple input options, the versatile X-15 opens up an array of display possibilities for any environment.

- > NeoV™ Optical Glass
- > Durable metal casing
- > Swift 4 ms response time
- > Crisp 3000:1 dynamic contrast ratio
- > High 320 cd/m² brightness
- > DVI ready for high quality signal
- > Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- > Auto-adjustment for optimal settings
- > Kensington® security socket
- > VESA standard wall mount
- > Available colours: black, white



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays



X-15

Specifications		X-15
Panel	Panel Type	TFT LCD
	Panel Size	15.0" (381 mm)
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297 mm
	Brightness	320 cd/m ² (Typical)
	Contrast Ratio	3000:1 (DCR)
	Viewing Angle (H/V)	140°/125° (Typical)
	Display Colour	16.7M
	Response Time	4 ms (GTG)
Panel Life Time	50,000 hrs (Minimum)	
Frequency (H/V)		H: 30 kHz - 60 kHz V: 56 Hz - 75 Hz
Max. Pixel Clock		80 MHz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
	S-Video	4-Pin Mini Din S-Video
	CVBS	CVBS Jack
Power	AC-DC Adaptor	External
	Power Consumption	AC 100 - 240 V, 50 - 60 Hz < 36 W (on) < 2 W (Stand-by) < 1 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	> 9H
Plug & Play	VESA	DCC 2B, DCC/GI
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 mm)
Tilt	Tilt	0° ~ +20°
Dimensions	Product (W x H x D)	380 x 359 x 155 mm (15.0" x 14.1" x 6.1")
	Packaging (W x H x D)	477 x 445 x 217 mm (18.8" x 17.5" x 8.5")
Weight	Product Weight	4.8 kg (10.6 lbs)
	Packaged Product Weight	7.0 kg (15.4 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/Baurt, CB, GOST-R, FCC, CE, BSMI, WEEE, RoHS, Vista/Basic, REACH
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), power cord, power adaptor, 15-Pin D-Sub cable, 24-Pin DVI-D cable, S-Video cable, CVBS cable




Available in black or white



Front-panel keypad with Input Select, Screen Menu, Contrast and Brightness controls for quick adjustments



Wide range of I/O connectors for flexibility and expandability in endoscopic video installations



NeoV™ Optical Glass and durable metal casing for water, dust and scratch resistance